

Charging cable Mode3 Typ2 32A 3ph 7,5m



Part number	08 91 409 0102 A0
Specification	Charging cable Mode3 Typ2 32A 3ph 7,5m
HARTING eCatalogue	https://b2b.harting.com/08914090102A0

Image is for illustration purposes only. Please refer to product description.

Identification

Element	Charging cable
Specification	Straight
Charging mode	Mode 3
Connector 1	Type 2 Female (Vehicle side)
Connector 2	Type 2 Male (infrastructure side)
Version	
Cable length	7.5 m
Termination method	Crimp termination
Core structure	5x 6 mm² + 0.5 mm²
Core structure Number of phases	5x 6 mm ² + 0.5 mm ² 3
Number of phases	3
Number of phases Number of contacts	3 7
Number of phases Number of contacts Number of signal contacts	3 7 2
Number of phases Number of contacts Number of signal contacts Number of power contacts	3 7 2 5 Signal: CP, PP

Technical characteristics

Rated current (signal)	2 A
Rated voltage (signal)	30 V
Rated current (power)	32 A

Page 1 / 3 | Creation date 2021-03-26 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Automotive GmbH | Marienwerderstraße 2 | D-32339 Espelkamp | Germany



Technical characteristics

Rated voltage (power)	480 V
Type of current	AC
Charging power	22 kW
Coding resistance	220 Ω between PE and PP
Ambient temperature	-30 +50 °C in operation -40 +80 °C storage/transport
Air pressure	≥540 hPa ≈ 5000 m
Insertion force	<100 N
Withdrawal force	<100 N
Mating cycles	≥10,000
Degree of protection acc. to IEC 60529	IP44
Cable diameter	16.5 mm ± 0.3 mm
Minimum bending radius	9x Cable diameter (repeated bending)
Conductor resistance @ 20 °C	≤3.3 Ω/km @ 6 mm² ≤39 Ω/km @ 0.5 mm²

Material properties

Material (insert)	Polyamide (PA)
Colour (insert)	Black
Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
Material (hood/housing)	Polyamide (PA)
Colour (hood/housing)	Black
Material (cover)	Thermoplastic polyurethane (TPU)
Material (cable)	TPE-U
Colour (cable)	Black
Material flammability class acc. to UL 94	V-0

Specifications and approvals

Specifications	IEC 62196-2 IEC 62893
Approvals	VDE
Commercial data	
Packaging size	1

Page 2 / 3 | Creation date 2021-03-26 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Automotive GmbH | Marienwerderstraße 2 | D-32339 Espelkamp | Germany



Commercial data

Net weight

Country of origin

4 kg Romania

European customs tariff number

eCl@ss

85444991

27144705 Charging cable E-Mobility

Page 3 / 3 | Creation date 2021-03-26 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Automotive GmbH | Marienwerderstraße 2 | D-32339 Espelkamp | Germany